

# RIVERMARK

• VIVEASH •

STAGE 2 DESIGN GUIDELINES

# Street Appeal

## DESIGN ELEMENTS

1. All homes with garages accessed from the primary street are required to incorporate a minimum of two (2) of the following features to the primary elevation:
  - A gable
  - A gabled garage
  - A garage setback of 1.5m or more from the outside wall of a habitable room
  - The external walls of a portico, verandah or main roof of the dwelling are a minimum of 3c higher than the garage external walls
  - A balcony
  - A porch/portico with a minimum depth of 1.2m
  - A verandah with minimum dimensions of 1.2m by 2.5m
  - Non-standard brick bonding
  - A planted trellis over the garage door to the extent of the opening as a minimum
2. All homes with garages accessed from a secondary street or rear laneway (Lots 44, 46 and 53-60 inclusive) are to incorporate a minimum of two (2) of the following features to the primary elevation:
  - A gable
  - A porch/portico with a minimum depth of 1.2m
  - A verandah with minimum dimensions of 1.2m by 2.5m
  - Non-standard brick bonding
3. For lots on a corner, the following are mandatory requirements:
  - On secondary streets, there must be a major opening from a habitable room forward of the fence line.
  - The materials and colours from the primary elevation must continue along the secondary street to the fence line at a minimum.

## WINDOWS

4. Homes shall incorporate at least one habitable window overlooking the primary street and/or public open space where the public open space is deemed the primary elevation.
5. Roller shutters are not permitted to windows visible from the primary or secondary elevation.

## ENTRY WAY

6. The entryway must be visible within the primary or secondary street elevations.
7. The entry must contain glazing either within the door or adjacent to the entry door.

**GARAGES, DRIVEWAYS AND CROSSOVERS**


8. The driveway and crossover must be completed prior to occupancy and be constructed with either brick paving, liquid limestone or exposed aggregate. Grey concrete is not permitted.
9. Garages are required to be enclosed. Carports are not permitted.
10. Garages must be setback a minimum of 0.5m behind the dwelling (excludes portico, verandah or balcony).
11. On lots wider than 18m where an additional single garage is proposed, the additional garage is required to be setback from the double garage by at least 0.5m
12. The garage door colour must match or complement the front elevation to reduce its dominance within the street elevation. Black and translucent doors are not permitted.

**BOUNDARY WALLS**

13. Walls built on the boundary must be finished to match the adjacent front or side walls.
14. Any part of a boundary wall that is visible from the street shall be finished in the same manner as the primary elevation.

**ROOFS**

15. A minimum roof pitch of 24.5 degrees is required.
16. Eaves are required to be 350mm.
17. Eaves are required to any habitable rooms on the primary elevation. (Exemption for gabled walls)
18. Gables are required to have a minimum 200mm overhang.
19. Metal and flat profiled roof (shingle style) tiles are permitted.
20. The roof colour selection must demonstrate an absorbance value of 0.6 or less.
21. Permitted roof colours are depicted in the colour palette. Tiled roofs are permitted in colours that match this palette.




# Colours & Materials

22. All elevations or portions of elevations visible from public view shall be finished in the same manner as the primary elevation (including rear elevations to laneway lots).
23. All homes are to incorporate face brick into the walls on the primary street elevation or within the landscape design by way of a letterbox, fence, planters.
24. Walls on the primary street elevation must include at least two (2) different colours and two (2) different materials. The secondary colour and/or material is to occupy at least 20% of the primary elevation. 2c brick is not permitted to the front elevation.
25. Material and colour finishes are required to continue at least 1m along the side elevation.
26. Colours are to be selected from the below/adjacent colour palette range. The palette suggests light colours for the main wall and earthy, natural colours as highlights. Black is not permitted.

PRIMARY COLOUR PALETTE



SECONDARY COLOUR PALETTE



# Keeping It Tidy

## FENCING

27. Front fencing is only permitted with the approval of the developer.
- 
28. Where front fencing is proposed it must be no higher than 1.2m and be constructed of masonry, open metal, timber or composite designs to match or complement the dwelling.

## PARKING

29. To maintain the streetscapes, the parking of caravans, campers, camp trailers, boats or commercial vehicles is required to be within a garage or behind a fence to screen them from the street.

## BINS

30. A dedicated location for bin storage is to be provided in the garage or behind the fence line. Bins must not be visible from the street or laneway whilst in the bin storage area.

## LETTERBOXES

31. A letterbox is required to the front of every home in a colour and material that matches or complements the dwelling. Letterboxes on single poles are not permitted.

## OUTBUILDINGS

32. Outbuildings of any size are not permitted except where the outbuilding is a lower height than the side boundary fence height or concealed from view by use of appropriate screening approved by the developer.

## SERVICE ELEMENTS

33. Air conditioning units must not be visible above the boundary fence and are preferably located at ground level. Roof-mounted air conditioning units must be colour matched to the roof.
- 
34. Antennas, satellite dishes, other roof-mounted structures and hot water units must not be visible from the street.
- 
35. All piped and wired services entering the site must be concealed from public view so as not to detract from the appearance of the dwelling. this includes external ducts being located within the building if visible from the primary or secondary street.
-

# Environmental Smarts

## ENERGY EFFICIENCY & RENEWABLE ENERGY

36. All houses must achieve a minimum 6-star NatHERS Energy Efficiency rating or equivalent.
- 
37. All stand-alone houses are required to have a rooftop solar photovoltaic system of at least 4.5 kilowatts professionally installed. Mounting rails must extend no more than 50mm beyond the frames of the solar modules.

## WATER EFFICIENCY AND CONSERVATION

38. To optimize efficient water usage, all homes are required to be fitted with:
- a. Minimum 3 Star WELS rated shower fittings
  - b. Minimum 6 Star WELS rated basin taps
  - c. Minimum 4 Star WELS rated taps generally, excluding outdoor and bath taps; and
  - d. Swimming pools must be fitted with a fixed retractable pool cover.

## WATER SOURCES

39. All toilets and washing machine cold taps must be installed with dual plumbing to allow for future connection to an alternative water source such as rainwater, without breaking the fabric of the building.
- 
40. Building plans must identify a suitable location for the installation of a rainwater tank with a minimum roof catchment area of 70m<sup>2</sup> delivered to that location. The location should allow simple connection to the dual plumbing network and allow for a tank to overflow into a soak well or other approved stormwater solution.

## CONSTRUCTION WASTE AND RECYCLING

Builders must adhere to the following requirements when constructing a home in Rivermark:

- 
41. Control potential for wind-blown waste by using an appropriate solid-sided storage receptacle on site;
- 
42. Follow applicable local government by-laws or building permit requirements; and
- 
43. Maintain a clean and tidy building site that discourages illegal dumping.

## LANDSCAPING

44. Synthetic Lawn is not permitted within any verge or front yard.
-

## Design Approval Process

### The Process

#### STEP 1

##### Design Your Home

Ensure your builder has a copy of these Design Guidelines.



#### STEP 2

##### Design Approval Application

Submit the following documents to the developer, Hesperia via email at:

[reviews@hesperia.com.au](mailto:reviews@hesperia.com.au)

- Completed Design Approval Application & Checklist
- Site Plans
- Elevation Plans
- Floor Plans
- Builders Material & Colour Schedule
- 7 star NatHERS Certification or Equivalent



#### STEP 3

##### Design Review

- If compliant with the Design Guidelines, the application will be approved by Hesperia and returned to the applicant.
- If the application requires amendments to fully comply with the Design Guidelines, Hesperia will provide written advice on areas of non-compliance so that amendments can be made, and the application resubmitted for approval.



#### STEP 4

##### Building Permit

After Hesperia has approved the application, you can make an application to the City of Swan for your building permit approval.

#### DEVELOPER APPROVAL:

- Approval by Hesperia does not constitute a local government planning or building license approval.
- Incomplete applications will not be accepted. All Submission Requirements must be provided.
- Any external changes to the home design or selections after the developer approval has been provided will need to be submitted for developer approval.
- Hesperia's approval is based on compliance with the Design Guidelines and is at the sole discretion of Hesperia.
- These Design Guidelines do not replace or override the statutory planning requirements of the City of Swan.
- Where a design proposal is consistent with the vision for Rivermark but is not entirely compliant with these Design Guidelines, Hesperia may approve the design on its merit. This does not create a precedent and all design variations will be assessed on an individual basis.

# RIVERMARK

• VIVEASH •

## Design Application & Checklist

LOT OWNER	APPLICANT
Name:.....	Name:.....
Phone:.....	Phone:.....
Address:.....	Address:.....
Email:.....	Email:.....
State:..... Postcode:.....	State:..... Postcode:.....

SUBMISSION REQUIREMENTS	DESIGN VARIATION RATIONALE
All applications must include: Site Plan <input type="radio"/> Floor Plans Elevation Plans <input type="radio"/> Builders Material and Colour Schedule <input type="radio"/> 7 Star NatHERS Certification or Equivalent <input type="radio"/>	For non-conforming designs provide a list of measures to ensure that the Design Guidelines are being upheld or improved.  ..... ..... ..... ..... .....

DECLARATION
All Statements made in this application are true and correct.
Applicant/Lot Owner Signature:..... Date:.....
Print Name:.....

## Checklist

This checklist is provided to assist with your application.  
Full design requirements can be found in the contract of sale.

STREET APPEAL	Yes ✓	No ✓	N/A ✓
1. Primary elevation includes a minimum of one of the following architectural features:			
• Balcony			
• Portico			
• Verandah			
• Gable			
• Non-standard brick bonding as a feature wall			
• Other: .....			
2. If the lot is less than 14m wide and the garage is accessed from the primary street a minimum of one of the following elements is incorporated:			
• A gabled garage			
• A planted Trellis over the garage door to the extent of the opening as a minimum			
• A garage setback of 1.5m or more from outside wall of main internal room of dwelling			
• Cars are parked within a pergola which is screened on at least two sides			
• The external walls of a portico, verandah or main roof of the dwelling are a minimum of 3c higher than the garage external walls			
• The garage is contained within a double story and contains a balcony or Juliette balcony over the garage.			



	Yes ✓	No ✓	N/A ✓
<b>3. Face brick is incorporated into primary elevation by its use in one of the following:</b>			
• Walls of the primary elevation			
• Letterbox			
• Planters			
• Fence			
• Other: _____			
<b>4. The primary elevation incorporates two different colours and materials. Where the secondary colour and/or material occupies at least 20% of the elevation.</b>			
Primary Material:			
Secondary Material: _____ % of elevation			
Primary Colour:			
Secondary Colour: _____ % of elevation			
<b>5. Material and colour finishes change at re-entrant corners and continue at least 1m alongside elevation.</b>			
<b>6. If the lot is on a corner, a major opening from a habitable room forward of the fence line addresses the secondary street and wall materials continue to the fence line as a minimum.</b>			
<b>7. Roof pitch is a minimum of 25 degrees.</b>			
<b>8. An eave overhang of at least 350mm is provided to habitable rooms, except where a habitable room extends within the eave overhang.</b>			
<b>9. Any gables have minimum 200mm overhang.</b>			
<b>10. The roof material and colour complies with Design Guidelines.</b>			
Material:			
Colour:			
Absorbance Value:			
<b>11. A feature window of at least 1.5sqm is provided to the primary elevation.</b>			
<b>12. Windows to front elevation are fixed, awning, casement, double hung or louvred.</b>			
<b>13. The entry way is visible from the primary or secondary street elevation.</b>			
<b>14. The entry door contains glazing, or a sidelight is incorporated adjacent to the door.</b>			
<b>15. An enclosed garage is provided.</b>			
<b>16. The garage is setback behind the dwelling alignment by at least 0.5m.</b>			
<b>17. Garage door colour:</b>			
<b>KEEPING IT TIDY</b>			
<b>18. Where front fencing is proposed, it is depicted on plans and is less than 1.2m in height.</b>			
Fencing materials:			
Fencing colour:			
<b>19. Driveway &amp; crossover will be completed prior to occupancy.</b>			
Driveway material:			
Driveway colour:			
<b>20. Walls built on a side or rear boundary are finished to match the dwelling walls adjacent.</b>			
<b>21. Bin storage that is not visible from the street is provided.</b>			
<b>22. All service elements are concealed from the street in accordance with design guidelines.</b>			

ENVIRONMENTAL SMARTS	Yes ✓	No ✓	N/A ✓
<b>23.</b> The dwelling achieves a minimum 6 star NatHERS Energy Efficiency rating or equivalent.			
<b>24.</b> A rooftop solar system of at least 4.5kw is provided or indicated as by owner.			
<b>25.</b> To optimise efficient water usage the following fittings are provided:			
• Minimum 3 Star WELS rated shower fittings			
• Minimum 6 Star WELS rated basin taps			
• Minimum 4 Star WELS rated internal taps (excluding bath taps)			
• Swimming pool will be fitted with a fixed retractable pool cover			
<b>26.</b> All toilets and washing machine cold taps will be installed with dual plumbing to allow for future connection to an alternative water source such as rainwater, without breaking the fabric of the building.			
<b>27.</b> Building plans identifies a suitable location for the installation of a rainwater tank with a minimum roof catchment area of 70m <sup>2</sup> delivered to that location.			

## Approval

APPROVED
<p>Design approval is granted based on the application and plans submitted.</p> <p>On behalf of Hesperia:..... Date:.....</p>



RIVERMARK.COM.AU  
INFO@RIVERMARK.COM.AU

**HESPERIA**

All the information in this document is published in good faith and for general information purposes only. Rivermark does not make any warranties about the completeness, reliability and accuracy of this information and does not accept legal liability or responsibility for any loss or damage incurred by the use of, reliance on or interpretation of the information contained in this document. All information plans, images, representations and artists impressions of a proposed development or project are indicative only and are subject to final design, specifications, all relevant consents, approval and actual construction. Whilst every care has been taken in relation to the accuracy of the information on the Website, no warranty is given or may be implied.